

NV120-T1310-T1310-10

Dual Channel Optical Transmitter for UHDTV Video applications

Data Sheet



Description

The NV120-T1310-T1310-10 is a Small Form Factor Pluggable (SFP+) LC dual channel optical transmitter. The unit is specially designed to meet SMPTE ST 2082-1 and to give robust performance when SDI pathological signals are present. All SD-, HD-, 3G-, 6G and 12G-SDI signal formats are supported. It is made with AutoSFP® enabled functionality to fit the miniHUB product range.

Features

- AutoSFP® enabled functionality
- Supports 4k and 8k UHDTV
- Compliant to SMPTE ST 2082-1, ST 2081-1, 424M, 292M, 297-2006
- Excellent performance with SDI-Checkfield test signal
- 1310nm DFB laser
- Typical Link lengths at 11.88Gbps:
 - 0.5 to 10km @ 9μm SMF
- Non-MSA Video compliant pinning
- SFF-8472 diagnostic features
- Hot-pluggable
- Class 1 21CFR and IEC60825-1 laser safety compliant
- Pb-free and RoHS compliant
- Available with extended temperature

Part Number Options

Part Number	Temperature *)
NV120-T1310-T1310-10	-5°C to +55°C

*) Rated temperature for the complete miniHUB.

Absolute Maximum Ratings

Absolute maximum ratings are those values beyond which functional performance is not intended, device reliability is not implied, and damage to the device may occur.

Parameter	Minimum	Maximum	Unit
Storage temperature (non-operating)	-40	+85	°C
Relative Humidity (non-condensing)	5	95	%
Supply voltage (Vcc)	0	3.6	V

Recommended Operating Conditions

Parameter	Minimum	Typical	Maximum	Unit
Case operating temperature:	-5		+70	°C
Relative Humidity (non-condensing)	5		90	%
Supply voltage (Vcc)	3.15	3.3	3.45	V

Electrical Characteristics

Parameter	Minimum	Typical	Maximum	Unit
Power dissipation			1700	mW
Data rate	0.27		11.88	Gbps

Transmitter Optical Characteristics

Parameter	Minimum	Typical	Maximum	Unit
Transmitting circuit fiber	Single Mode (9/125µm), Multi Mode compatible			
Light source	Fabry-Perot laser			
Optical output power	-8.2		2	dBm
Optical extinction ratio	3.5			dB
Optical center wavelength	1260	1310	1355	nm
Spectral line width (-20dB)			1	nm
Typical link length with 9µm SMF:				
@ 11.88 Gbit/s	10			km
@ 2.97 Gbit/s	10	30		km

Norwia AS
Kilgata 12
3217 Sandefjord
Norway

Contact:
phone: +47 33 45 20 90
e-mail: info@norwia.no
web: norwia.com

